

# Nexa Frontier

Core 2 Duo Touch POS Terminal



The Nexa Frontier is a Core 2 Duo 2.8Ghz POS Terminal that is more than capable of handling the most demanding of POS applications.

Featuring a slimline design, tool free servicing, ample ports and accessories, the Frontier is also extremely servicable and flexible.



Very small footprint, plus the screen is able to fold down 90 degrees.



24V Printer power port. No need for a separate printer power supply.



Rear LCD option for customer advertising



# NEXA

Visit [www.nexapos.com](http://www.nexapos.com) to find out about other exciting NEXA products!

# Nexa Frontier

## High Performance Touch POS Terminal

### LCD & Touch Panel

LCD Panel  
15" TFT

MAX. Resolution  
1024 X 768 (Default)

Brightness  
250 cd /m2

Touch Screen  
5 wire Resistive (RS232 type)

### System Configuration

CPU  
Intel Core 2 Duo 2.8GHz Processor

Chipset  
Intel 945GC+ ICH7

Main Memory  
240-Pin DDR2 RAM\*2 slot, up to 2GB

HDD  
1 x 3.5" SATA HDD

Compact Flash Card  
1 x Bootable Compact Flash Card socket ( Type I/II )

Optical Device  
1 x Slim type CD-ROM/DVD-ROM/ COMBO (Optional )

### I/O Ports

Parallel Port 1 x LPT Port ( SPP/EPP/ECP ). IRQ  
and address selectable

Serial Port  
3 x DB-9 COM Ports. All with DC 5V/12V output on  
Pin 9 selectable

USB Port  
6 x USB2.0 Ports ( 4 x rear, 2 x front)

LAN Port  
1 x (10/100/1000M bps Auto)

Keyboard / Mouse Port  
1 x PS/2 Keyboard, 1 x PS/2 Mouse

Audio Port  
1 x MIC In

Cash Drawer Port  
1 x RJ-11 Port (12V/24V selectable )

Analog VGA Port  
1 x D-SUB-15 connectors

Speaker Output  
2 x 1W stereo Speaker

DC Output  
1 x DC Jack 12V Output for 2nd Display  
1 x Hosiden 24V Output for Thermal Printer

### Powering System

Power Supply  
ATX 250W Internal Power Supply. AC 100 to 240V Full Range

LED Indicators  
4 x LED Indicators ( Standby 5V / ATX on / HDD / LAN Status)

### Physical Dimensions

Dimension  
350 ( L ) x 350 ( W ) x 350 ( H )mm

Weight  
10Kg

### Safety & Environment

Product Certification  
CE, FCC Certificated

Operation Temperature  
0°C to 40°C

Storage Temperature  
-25°C to 70°C

OS Compatibility  
DOS / WINDOWS 2000 / XP / XPE / Vista / Windows 7 / WEPOS /PO



# NEXA

Visit [www.nexapos.com](http://www.nexapos.com) to find out about other exciting NEXA products!