

Specification IT-6320DPM

Specifications	IT-6320DPM	
Reading distance	Narrow width (SR)	Depth of Field
	13 mil Linear	0 - 6.2 cm
	5 mil 2D	0 - 3.6 cm
	10 mil 2D	0 - 5.5 cm
	20 mil 2D	0 - 9.5 cm
Reading Direction	Omni-Directional	
illumination	Integrated diffuser; bright- and Dark-field LED's	
Aiming	Horizontal green light bar aimed at the centre field of view	
Pitch Angle	+/- 34deg.	
Skew Angle	+/- 34 deg	
Sensor	1280 x 960 high resolution pixel array	
Trigger	via trigger switch in the handle or via software in the PC	
Additional Outputs	Multifunctional LED and beeper to indicate good read, device status or errors	
Interfaces	RS-232	
	USB	
Symbologies support	Data Matrix, QR Code, Interleaved 2 of 5, Code 93, Code 39, Code 128, UPC-A & E, EAN-8 & 13	
Warranty	18 Months Factory Warranty (not on cable, conditions apply)	
Sealing	Reader IP54, Base station for 6320 IP41	
Operating Temperature	0°C to +50°C	
Humidity	0 to 95% non-condensing	
Mechanical Shock	Operational after 25 Drops from 2m to Concrete	