

# PRECISION! HIGH PERFORMANCE! 8.64" PRINT WIDTH



## TTP-384M INDUSTRIAL THERMAL TRANSFER BAR CODE PRINTER

The TSC TTP-384M wide format thermal transfer label printer is the newest addition to the TSC Industrial Printer family. It is specifically designed for applications that need to print high quality wide format thermal transfer or direct thermal labels. These applications include compliance labeling, brand marketing, warning signs, rack storage signs for inventory control, drum labeling and a host of other signage solutions. Customers can use the TTP-384M to print wide lateral bar codes more efficiently without having to rotate the image.

Never before have so many standard features been packed into a wide web label printer at such an affordable price. The industrial class TTP-384M can manage label widths up to 9.5" with a maximum print width up to 8.64" wide at 300 dpi high resolution.

TTP-384M standard features include a large LCD display, 8MB Flash memory, 32MB SDRAM, built-in internal Ethernet 10/100 print server, USB 2.0, PS/2 keyboard interface, Centronics, RS-232C, and an SD Flash memory card slot that allows users to inexpensively add up to 4GB of additional memory storage. The print mechanism supports up to a 600

meter ribbon length and a full 8.2" OD media roll. All of this offered at an affordable price, and with a two-year limited warranty.

With a "Simple, Easy-to-use, and Affordable" design concept, the TTP-384M delivers both performance and value to the customer. The printer's large LCD control panel makes it easy to manage printer settings; the center-bias label handling mechanism makes media loading and adjustment easy; the built-in Ethernet print server allows IT management to control and monitor the printer remotely; and the precise aluminum die-cast chassis ensures lifetime print quality and durability.

TTP-384M is an ideal printer for:

- ▶ Compliance labeling for shipping and receiving
- ▶ Brand marketing featuring graphics, logos and texts
- ▶ Pallet labeling
- ▶ Inventory control labeling
- ▶ Warning labels
- ▶ Drum labeling
- ▶ Custom signage
- ▶ Multiple-up labels (two or three labels across)



*Value • Performance • Support*

# TTP-384M

## INDUSTRIAL THERMAL TRANSFER BAR CODE PRINTER



### SPECIFICATIONS

Printer model	TTP-384M
Resolution	300 DPI
Printing method	Thermal Transfer and/or Direct Thermal
Max. print speed	2, 3, 4 ips
Max. print width	219.5 mm (8.64")
Max. print length	1270 mm (50")
Enclosure	Die-cast chassis, sheet metal structure with clear media view window
Physical dimension	440 mm (W) x 336 mm (H) x 504 mm (D) or 17.32" (W) x 13.23" (H) x 19.84" (D)
Weight	23.2 kg
Label roll capacity	208.3 mm (8.2") OD
Ribbon	600 meter long, 1" core (ink coated outside)
Ribbon width	110 mm ~ 254 mm (4" ~ 10")
Processor	32-bit high performance processor
Memory	<ul style="list-style-type: none"> <li>● 8 MB Flash memory</li> <li>● 32 MB SDRAM</li> <li>● SD Flash memory card slot (up to 4 GB memory expansion)</li> </ul>
Interface	<ul style="list-style-type: none"> <li>● RS-232C (2400 - 115200 bps)</li> <li>● Centronics (SPP mode)</li> <li>● USB 2.0 client (full speed)</li> <li>● PS/2 keyboard interface</li> <li>● Internal Ethernet 10/100 print server</li> </ul>
Power	Internal switching power supply <ul style="list-style-type: none"> <li>● Input: 90-264VAC, 47-63Hz</li> <li>● Output: 24V, 14.58A, 350W</li> </ul>
LCD display	Graphic type, 128 x 64 pixel, with back light
Operation switch, button	1 power switch, 6 operation buttons
Sensors	<ul style="list-style-type: none"> <li>● Transmissive/ gap sensor (position adjustable from 4" ~ 8")</li> <li>● Reflective black mark sensor (position full web adjustable)</li> <li>● Transmissive ribbon end sensor</li> <li>● Ribbon encoder sensor</li> <li>● Head open sensor</li> </ul>
Real time clock	Standard
Internal fonts	<ul style="list-style-type: none"> <li>● 8 alpha-numeric bitmap fonts</li> <li>● Monotype Imaging® true type font engine with 1 CG Triumvirate Bold Condensed scalable font</li> </ul>
Bar code	1D bar code Code 39, Code 93, Code 128UCC, Code 128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec
Font and barcode rotation	0, 90, 180, 270 degree
Command set	TSPL-EZ™
Media type	Continuous, die-cut, fan-fold, tag, notched, black mark, perforated
Media width	101.6 ~ 241.3 mm (4" ~ 9.5")
Media width (cutter mode)	101.6 ~ 215.9 mm (4" ~ 8.5")
Media thickness	0.06 ~ 0.254 mm (2.36 ~ 10 mil)
Media core diameter	76.2 mm (3")
Label length	25.4 ~ 1270 mm (1" ~ 50")
Environment condition	<ul style="list-style-type: none"> <li>● Operation: 5°C ~ 40°C, 20% ~ 85% non-condensing</li> <li>● Storage: -40°C ~ 60°C, 5% ~ 90% non-condensing</li> </ul>
Safety regulation	FCC Class A, CE Class A, UL, CUL, TUV/Safety
Environmental concern	Comply with RoHS, WEEE
Accessories	<ul style="list-style-type: none"> <li>● Windows labeling software CD disk</li> <li>● USB port cable</li> <li>● Power cord</li> <li>● Ribbon take-up paper core</li> </ul>
Limited warranty	<ul style="list-style-type: none"> <li>● Printer: 2 years</li> <li>● Print head: 1 million inches (25 km) or 12 months which comes first</li> <li>● Platen: 50 km</li> </ul>
Factory options	GPIO interface
User options	<ul style="list-style-type: none"> <li>● Cutter module, Max. paper width: 215.9 mm (8.5"), life of cuts: 500,000 cuts (paper weight 200 g/m²)</li> <li>● Bluetooth module</li> <li>● KP-200 Plus keyboard</li> <li>● KU-007 Plus programmable smart keyboard</li> </ul>

