



2 inch Barcode Label Printer

# SLP-DX220

a Better Solution for your Business™



Standard

Peeler

Auto-cutter

## FEATURES

### Dual interface

- Standard: Serial + USB
- Optional: Ethernet + WLAN\* + USB



### User-friendly Design

- Easy paper loading with adjustable paper guide
- Pause and cancel function-keys




function-keys



### Powerful Compatibility

The SLP-DX220 is fully compatible with market-leading programming language; SLCS, BPL-Z™, BPL-E™.



BPL-Z™

BPL-E™

### Label Artist™

Bixolon provides its custom label design program as bundle. It supports **database** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

BR-SLP-DX220-EN-JUL13

Copyright © 2013 BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

## SPECIFICATIONS

### Printer Specifications

**Print Method:** Direct Thermal

**Print Speed:** SLP-DX220: Up to 6 ips (152 mm/s) / SLP-DX223: Up to 4 ips (100 mm/s)

**Print Resolution:** SLP-DX220: 203 dpi / SLP-DX223: 300 dpi

**Print Width:** SLP-DX220: Up to 54 mm / SLP-DX223: Up to 56.9 mm

**Print Length:** 6 ~ 2000 mm

**Media Sensor:** Transmissive, Reflective (adjustable), Head open

### Media Characteristics

**Media Type:** Gap, Black Mark, Notch, Continuous, Fan-Fold

**Media Width:** 15 ~ 60 mm

**Media Roll Diameter:** Up to 130 mm

**Media Thickness:** 0.06 ~ 0.20 mm

**Supply Method:** Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxH):** 120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)

**Weight:** 1.36 kg (2.99 lbs.)

**Power:** EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

### Performance Characteristics

**Memory:** 64MB SDRAM, 128MB Flash

**Interface:** Dual Interface

Standard: Serial+USB V2.0 HS

Optional: Ethernet+WLAN\*+USB V2.0 HS

\* WLAN: 802.11b/g/n USB dongle type (optional)

### Environment Characteristics

**Temperature:** Operating: 0 ~ 40°C (32 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity:** Operating: 10 ~ 80% RH

Storage 10 ~ 90% RH

### Software

**Emulation:** SLCS, BPL-Z™, BPL-E™

**Driver/Utility:** Windows Driver (Euro Plus/Seagull), OPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB / Ethernet Driver, Utility Program, Label Artist™

**SDK:** Android SDK

### Fonts / Graphics / Symbolologies

**Character Sets:** · 10 SLCS Resident Bitmap Fonts

· One SLCS Resident Scalable Font

· 16 BPL-Z™ Resident Bitmap Fonts

· One BPL-Z™ Resident Bitmap Font

· 5 BPL-E™ Resident Bitmap Fonts

· 23 Code Page

· Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

**Graphics:** Supporting user-defined fonts, graphics, formats, and logos

**Barcode Symbolologies:** 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB  
2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39

### Options

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock)

**BIXOLON®**

www.bixolon.com



**BIXOLON Co., Ltd.**

7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

Authorised Australian Distributor:

Goodson Imports Pty Ltd

9 Liberty Road

Huntingwood NSW 2148

Representation in all main States and New Zealand

Ph: 02-8875 4544 Fax 02-8875 4588

www.goodson.com.au