

# J2 615

## Integrated Touch Terminal



### Key Features

- > 15" narrow border PCAP touchscreen
- > Ultra slim & Fanless
- > Aesthetic metallic design
- > 350° swivel & ergonomic design
- > MSR / iButton / Fingerprint reader / NFC reader / 2D scanner / 2nd display / Customer display available



### Benefits

- > Ultra-slim
- > Swivel and tilt monitor
- > Windows or Android compatible
- > Modular peripherals
- > Multiple mounting options

## J2 615 - Ultra-slim Swivel POS

### Stylish - Compact - Versatile

The J2 615 provides retail and hospitality businesses with a stylish, modern integrated touch terminal solution.

It's slimline design is created by separating the CPU from the monitor, allowing for a more compact monitor head.

The CPU is located in the base of the terminal and in doing so expands mounting options. Place the J2 615 on a desktop or mount the monitor to a desk with the CPU base under the counter for a cable free look.

The swivel monitor base allows for a full 350° rotation making the J2 615 the perfect POS choice where customer interaction on screen may be required or access to the terminal from both sides of a counter is needed.

A broad range of processors are available to suit your power needs from Qualcomm 450 to Intel i3-7020U. 8Gb of RAM comes standard with all J2 615 terminals.

Ports are aplenty with 7 x USB ports, 2 x

powered Serial ports, cash drawer port and 2 x display ports.

Choose from a range of optional peripherals including MSR, fingerprint reader, NFC, iButton, barcode scanner, customer display, 2nd display and powered USB box.

Supported operating systems include Android 9.0, Windows 10 IoT and Linux.



### SPECIFICATION

<b>System</b>	Motherboard	F14	D84U
	Processors	Qualcomm® 450	Intel® i3-7020U
	Memory	8GB	8GB
	Storage	32GB eMMC	128GB SSD
	Supported OS	Android 9.0	Windows 10 IoT Enterprise, Linux
<b>I/O Ports</b>	<b>Front Side</b>		
	USB	1x USB2.0	1x USB2.0
	Power Button	1	1
	<b>Rear Side</b>		
	USB	1x USB3.0 (Type C)	2x USB3.0 (Type C)
		1x Micro USB	2x USB3.0
		2x USB3.0	2x USB2.0
		2x USB2.0	
	Serial Port	2x DB9 (Powered RS232) (default: 0V; COM1/COM2: 0V, 5V, 12V)	2x DB9 (Powered RS232) (default: 0V; COM1/COM2: 0V, 5V, 12V)
	LAN	1x RJ45	1x RJ45
	Cash Drawer	1x RJ11	1x RJ11
FeDP	2x Flytech Proprietary MiniDP	2x Flytech Proprietary MiniDP	
DC Jack	1x 4PIN DIN (with latch)	1x 4PIN DIN (with latch)	
<b>Display</b>	Size and Resolution	15.1" 1024x768	15.1" 1024x768
	Touch Screen	True-Flat PCAP multi-touch	True-Flat PCAP multi-touch
<b>Audio</b>	Internal Speaker	1 x 3W	1 x 3W
<b>Power</b>	Power Adaptor	65W/19V	120W / 19V
<b>Certificate</b>	EMC & Safety	FCC Class A, CE Mark, LVD	FCC Class A, CE Mark, LVD
<b>Environment</b>	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
<b>Dimensions</b>	W x D x H	327 x 200 x 303 mm (12.8" x 7.9" x 12")	327 x 200 x 303 mm (12.8" x 7.9" x 12")
<b>Options</b>	Wireless LAN + BT	BT4.1 WiFi 802.11 b/g/n/ac	WiFi+BT USB dongle
	MSR	3-Track MSR	3-Track MSR
	Fingerprint	Fingerprint Reader	Fingerprint Reader
	NFC	-	NFC Reader
	iButton	iButton	iButton
	Scanner	2D Scanner	2D Scanner
	Customer Display	LCM display 2 x 20 characters	LCM display 2 x 20 characters
	2nd Display	11.6" 2nd display with touch	11.6" 2nd display with touch
	Powered USB box	2x 12V Powered USB	2x 12V Powered USB
		1x 24V Powered USB	1x 24V Powered USB
	Cable	Converter cable for FeDP to VGA Converter cable for FeDP to HDMI	Converter cable for FeDP to VGA Converter cable for FeDP to HDMI
		Converter cable for FeDP to HDMI	Converter cable for FeDP to HDMI
	Thermal Solution	-	Heatsink kit

### Contact

#### AURES Technologies

Unit 6 83/85 Boundary Road,  
Mortdale NSW 2223 | Australia  
Ph. +61 2 9584 5222

